



Free Standing Dri-Air Regulator



Your choice of connectors can be supplied at extra cost.
Please Specify type with order

Airflow
50 cfm capacity
(24 litres per second)

Dimensions

Length 410mm
Width 220mm
Height 320mm
Weight 9.5 Kgs. (exc-fittings)

**Connectors, splitter and taps
fitted for illustrative purposes
only.**

**Larger capacity units made to
order**

Removes over 95% of the water found in airlines.

Moisture in the air is compressed and turned into **water droplets in the airflow**, which if allowed to will quickly clog and destroy expensive air tools. This is particularly so in the case of **outdoor compressors which draw in cold damp air**.

The Cengar Dri-Air unit removes the water, and other fluids such as compressor oil, and automatically discharges to a suitable container.

The clean dry air is then supplied with a mist of air tool oil such as **Cengar Green Oil** lubricating your air tool and protecting against further corrosion

An integral Pressure Regulator protects tools from being over driven.

The filter unit is rugged, stable, service free, and gives long life due to the use of non corrosive materials, and is ideal for site operations and workshops alike

For more information contact: -

Cengar Ltd. Springfield Works, Saddleworth Road, Halifax HX4 8LZ, U.K.
Tel: +44 (0)1422 377904 Fax: +44 (0)1422 377161

www.cengar.com Email: enquiries@cengar.com